

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : A61B 5/103	A1	(11) International Publication Number: WO 95/32666 (43) International Publication Date: 7 December 1995 (07.12.95)
-------------------------------------------------------------------	-----------	------------------------------------------------------------------------------------------------------------------------------

(21) International Application Number: PCT/US95/06626

(22) International Filing Date: 24 May 1995 (24.05.95)

(30) Priority Data:
08/250,152 26 May 1994 (26.05.94) US(71)(72) Applicant and Inventor: CURCHOD, Donald, B.
[AU/US]; 1023 Los Trancos, Portola Valley, CA 94028 (US).

(74) Agent: KING, Patrick, T.; Law Offices of Patrick T. King, 36 Seascapes Village, Aptos, CA 95003 (US).

(81) Designated State: JP.

Published


With international search report.

US 5,826,578

(54) Title: MOTION MEASUREMENT APPARATUS

(57) Abstract

This invention is an apparatus for measuring and visually displaying a user's body movement while performing a motion. Sensing means (22) such as a potentiometer, are coupled to the joints of a user in order to quantitatively detect movement of the user's body while performing a motion. The sensors (22) generate signals indicative of the motion and are received by processor means (30) which in turn connects to a display means (32) for graphically displaying at least one image representing the movement. A second image may be displayed with the first image for comparison purposes.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Larvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

5

MOTION MEASUREMENT APPARATUS

10 BACKGROUND OF THE INVENTION

1. Field of the Invention. The present claimed invention relates to movement of the human body. More specifically, the present claimed invention relates to quantitatively measuring
15 movements of the human body which occur while performing a motion.

2. Prior Art.

Monitoring or quantitatively measuring the movement of
20 the human body while performing a motion is essential in many fields such as, for example, sports instruction or physical therapy. However, many of the motions of interest are performed very quickly and make observation and analysis difficult or impossible. Furthermore, most prior art teaching or instruction techniques
25 are performed by observing or recording the motion of a performer and then analyzing the performer's body movement. That is, the performer's body movement is not analyzed or reviewed during the performance of the motion, but is instead delayed until after the performer has completed the motion. As a result, it is often
30 difficult to alter or correct aspects of the performer's body movement using prior art teaching or instruction techniques.

Additionally, many prior art systems for monitoring the movement of a human body employ complicated and costly detection systems. For example, prior art motion monitoring
35 systems commonly generate optical or acoustic signals which are directed towards the performer. Detectors then receive signals

reflected from the performer and use the reflected signals to analyze movement of the user's body. However, such systems are bulky, often taking up an entire room or even larger areas. In addition to their considerable bulk, such prior art systems are also
5 extremely expensive. Thus, many of the prior art systems for monitoring the movement of a human body are not well suited for personal private use. That is, the considerable cost, bulk, and complexity associated with prior art systems prohibits their use for most consumers.

10 Thus, the need has arisen for a compact, inexpensive system to monitor the movement of a human body while performing a motion, which does not require the complex detection systems found in the prior art, and which provides for approximate real time observation of the body movement of a
15 performer while performing a motion.

SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide a compact, inexpensive system to monitor the movement of a human body while performing a motion, which does not require the complex detection systems found in the prior art, and which provides for approximate real time observation of the body movement of a performer while performing a motion. The above object has been achieved by a compact structure wherein sensors are coupled to a user's body at joints of the user's body which are moved while a user performs a motion. The user's body movement, as quantitatively measured by the sensors, is graphically displayed on a display screen at approximately the same time the user performs the motion. Thus, by placing the display screen within view, the user is able to observe his or her body movements in real time, that is while he or she performs the motion. In so doing, the user is able to correct or alter body movements in order to more correctly perform the motion.

In another embodiment, the user's body movement, as quantitatively measured by the sensors, is graphically displayed on a display screen concurrently with a second image. The second image can represent a prior performance of the motion by the user, or can represent a performance of the motion by a second user, such as for example, a professional who performs the motion in an "ideal" manner. In so doing, not only is the user able to observe his or her body movements in real time, but the user is also able to compare those body movements to the ideal body movements of a professional, and adjust his or her own movements to match that ideal standard.

In still another embodiment, two different images representing separate prior performances of the motion by the user can be simultaneously displayed and compared on the display screen. In so doing, the user is able to see, for example, improvements or changes in his body movements when performing the motion.

BRIEF DESCRIPTION OF THE DRAWINGS

5 The accompanying drawings, which are incorporated in and form a part of this specification, illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention:

10 FIGURE 1 is a perspective view of a prior art motion detector.

15 FIGURE 2 is a perspective view of a golfer using a motion measurement apparatus constructed in accordance with the present claimed invention.

FIGURE 3 is a side view of a knee joint of a golfer having a sensor attached thereto in accordance with the present claimed invention.

20 FIGURE 4 is a perspective view of another embodiment of the present invention in which adjacent sensors are interconnected to form a single structure in accordance with the present claimed invention.

25 FIGURE 5A shows a series of images duplicating the body movements of a golfer which can be displayed on a display unit while the golfer performs a golf swing in accordance with the present claimed invention.

30 FIGURE 5B shows a series of images duplicating the body movements of a golfer displayed wherein the images are arranged side-by-side on a display unit while the golfer performs a golf swing in accordance with the present claimed invention.

35 FIGURE 6A shows another embodiment of the present claimed invention in which two images having differing body

positioning are displayed concurrently on a display unit in accordance with the present claimed invention.

FIGURE 6B shows the images of Figure 6A in which the two images have the same body positioning and are displayed concurrently on a display unit in accordance with the present claimed invention.

FIGURE 6C shows a "fan" type display of the position of the golf club of a golfer and the position of the golf club of a sample golfer at different times during a golf swing in accordance with the present claimed invention.

FIGURE 7 shows another embodiment of the present claimed invention in which two images are displayed concurrently and overly each other on a display unit in accordance with the present claimed invention.

FIGURE 8A and 8B show another embodiment of the present claimed invention in which the motion measurement apparatus of the present invention is utilized by the user in conjunction with a display as a "keyboard" or "mouse" in accordance with the present claimed invention.

FIGURE 9 is a side view of a knee joint in another embodiment of the present claimed invention in which a small vibrating mechanism is attached to a sensor located on the knee joint of a golfer in accordance with the present claimed invention.

FIGURES 10A-H are views of the structure of one embodiment of a motion measurement apparatus in accordance with the present claimed invention.

FIGURE 11A is a perspective view of an alternate arrangement of a motion measurement apparatus in accordance with the present claimed invention.

FIGURE 11B is a perspective view of an alternate embodiment of a motion measurement apparatus wherein the apparatus is used as a head mouse in accordance with the
5 present claimed invention.

FIGURE 12 is a perspective view of an alternate embodiment of a motion measurement apparatus wherein the apparatus includes gyroscopic means in accordance with the
10 present claimed invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred
5 embodiments of the invention, examples of which are illustrated
in the accompanying drawings. While the invention will be
described in conjunction with the preferred embodiments, it will
be understood that they are not intended to limit the invention to
these embodiments. On the contrary, the invention is intended to
10 cover alternatives, modifications and equivalents, which may be
included within the spirit and scope of the invention as defined by
the appended claims.

With reference now to Prior Art Figure 1, a prior art motion
detector 10 is shown. Prior art motion detector 10 is employed in
15 Prior Art Figure 1 to measure the body movements of a golfer 12
while golfer 12 performs a golf swing. As shown in Prior Art
Figure 1, prior art motion detector 10 occupies an entire room 14,
and requires the use of several signal generators and detectors 16.
Additionally, golfer 12 is only able to view his body movements
20 after he has performed the golf swing and his body movements
have been recorded.

With reference now to Figure 2, a motion measurement
apparatus constructed in accordance with an embodiment of the
present claimed invention for measuring body movements which
25 occur when performing a golf swing is illustrated. Although the
present embodiment specifically relates to an apparatus for
measuring body movements which occur while performing a golf
swing, the present claimed invention is also well suited to
measuring body movements which occur while performing
30 various other motions, such as, for example, a tennis stroke, other
sports related motions, or dance movements. In addition, the
present motion measurement invention is also well suited to
incorporating the user's body motion into, for example, a video
arcade game, or for converting the various movements of the
35 user's body to corresponding musical tones.

With reference still to Figure 2, a golfer 20 has inexpensive and compact sensors 22 attached to his body at joints which are moved while golfer 20 performs a golf swing. Sensors 22 are attached to the joints of golfer 20 such that sensors 22
5 quantitatively measure the movement of the joints of golfer 20 while golfer 20 performs the golf swing. Sensors 22 are attached to joints of golfer 20 in such a manner that sensors 22 do not interfere with the movement of the joints while golfer 20 performs a golf swing.

10 With reference next to Figure 3, an enlarged view of an example of a knee joint 24 of golfer 20 of Figure 2 having a sensor 22 attached thereto is shown. As shown in Figure 3, sensor 22 is attached to knee joint 24 in a manner such that knee joint 24 is able to move without interference from sensor 22. In the present
15 embodiment, rods 26 extending from sensor 22 are fastened above and below knee joint 24 using straps 28. As knee joint 24 straightens or bends, sensor 22 detects the movement of rods 26 and generates an electric signal indicative of the shift in position of knee joint 24. In so doing, quantitative measurement of the
20 movement of knee joint 24 and all other joints to which sensors 22 are attached is achieved. Although, potentiometers are used as sensors 22 in the present embodiment, the present claimed invention is also well suited to the use of numerous other types of sensors well known in the art such as, for example, stepper
25 motors, optical sensors, or magnetic sensors.

With reference still to Figure 3, sensors 22 quantitatively measure the movement of joints in more than one dimension where needed. That is, a sensor 22 located at, for example, the elbow of golfer 20 of Figure 2 measures both the amount of bending
30 of the elbow and also the amount of rotation which occurs between the elbow and the wrist as golfer 20 performs a golf swing. In so doing, all of the critical body movements of golfer 20 which occur during the performance of a golf swing can be quantitatively measured by sensors 22.

35 With reference next to Figure 4, another embodiment of the present claimed invention is shown in which adjacent sensors 22

are interconnected using, for example, metal tubing. That is, in the present embodiment, instead of having rods 26 of Figure 2 strapped to the leg of golfer 20 of Figure 2, rods 26 would extend and be attached to adjacent sensors. As shown in Figure 4, a tube
5 25 connects sensors 22 located at the hip and at the knee of golfer 20. Another tube 27 connects sensors 22 located at the ankle and knee of golfer 20. As a result, a single structure is formed wherein sensors 22 function as joints between connected tubes. By forming a single structure as set forth in the present embodiment,
10 golfer 20 of With reference again to Figure 2, a processor 30 receives and processes signals generated by each of sensors 22. The processed signals are then transmitted to a display unit 32. Display unit 32 then displays an image such as, for example, a stick figure which duplicates the body movements of golfer 20 as
15 golfer 20 performs a golf swing. That is, display unit 32 displays in approximately real time, an image which represents the body movements of golfer 20 as golfer 20 performs a golf swing. Therefore, by placing display unit 32 within view of golfer 20, golfer 20 is able to observe his body movements, as depicted by an
20 image on display unit 32, while golfer 20 performs a golf swing. In so doing, golfer 20 can immediately alter or correct his body positioning and/or body movements until he generates an image on display unit 32 which exhibits desired body position and/or body movements. Additionally, although processor 30 of Figure 2 is
25 shown located next to the body of golfer 20, processor 30 may also be contained within a small housing, not shown, and attached to the body of golfer 20 in a convenient location such as, for example, the back of golfer 20.

With reference next to Figure 5A, an example of a series of
30 typical images which can be displayed together as a group or individually on display unit 32 are shown. In the present embodiment, image 40 representing a side view of golfer 20 of Figure 2 is displayed on display unit 32. In operation, as golfer 20 prepares to use the present invention, golfer 20 would attach
35 sensors 22 of Figures 2-4 to his body and then calibrate sensors 22 and processor 30 according to the golfer's individual size and

dimensions. In the present embodiment, this calibration process only needs to be performed once. Next, golfer 20 would address the golf ball and observe the body position of image 40 on display unit 32. In so doing, golfer 20 would be able to observe any obvious
5 flaws or improper body positioning occurring while golfer 20 addresses a golf ball. As a result, golfer 20 is able to quickly "self-correct" his golf stance and alter his body positioning until image 40 is arranged in the proper or desired position. Likewise, as golfer 20 performs a golf swing, golfer 20 is able to observe image
10 40 on display unit 32 at each moment during the golf swing and immediately recognize and correct any imperfections in his body position or his body movements. That is, the present claimed invention provides for approximate real time observation of the body movement and positioning of a golfer while the golfer is
15 performing a golf swing. Thus, golfer 20 is able to receive immediate feedback and is better able to identify mistakes or imperfections in his golf swing.

With reference again to Figure 5A, although the present embodiment provides for approximate real time observation of an
20 image representing golfer 20, the present claimed invention is also well suited for storing the image representing the body movement and positioning of golfer 20 and displaying the image at a later time. By storing the image, golfer 20 of Figure 2 can either view the image immediately after performing the swing or wait
25 until a later more convenient time.

With reference still to Figure 5A, in another embodiment of the present invention multiple images such as, for example, images 40, 42, and 44 of golfer 20 are displayed at the same time on display unit 32. Images 40, 42, and 44 show the body position and
30 movement of golfer 20 from several different angles. Line 48 of image 46 depicts the path of the head of the golf club just prior to and after the golf club contacts a golf ball. Thus, golfer 20 is able to observe his body position and movements in real time from several different angles, and golfer 20 is able to observe the path of the club
35 head as it strikes a golf ball. Although the present embodiment, employs images such as images 40, 42, 44, and 46, the present

claimed invention is also well suited to numerous other types of images which can be graphically displayed on display unit 32. Furthermore, the present claimed invention is also well suited to displaying information such as club head speed, distance that a golf ball would be hit, or other relevant information on display unit 32.

With reference next to Figure 5B, the present invention is also well suited to displaying several images of the body position of golfer 20, wherein each of the images represents a different view of the body of golfer 20. As shown in Figure 5B, a right side view 40, a front view 42, and a left side view 43 may be displayed, for example, side-by-side. Although such views are shown in Figure 5B, the present invention is also well suited to displaying other views, and placing those views in different arrangements on display unit 32.

With reference next to Figure 6A, yet another embodiment of the present claimed invention is shown in which two images 50 and 60 are displayed concurrently on display unit 32. In the present embodiment, image 50 represents the body position and body movements of golfer 20 of Figure 2. Dotted image 60 represents a "sample" golfer whose body position and movements are stored in the memory of processor 30. Image 60 represents, for example, a stored record of the best previous golf swing of golfer 20, a golf swing of the instructor of golfer 20, a golf swing of a professional golfer, or a computer generated golf swing. Therefore, the present invention allows for real time observation by golfer 20 of his own golf swing, and also allows for real time comparison by golfer 20 of his golf swing with an "ideal" golf swing. Thus, golfer 20 is able to immediately alter his body position and movements during his golf swing so that his movements duplicate the body position and body movements of an ideal golfer. Although image 60 is dotted in the present embodiment, the present invention is also well suited to numerous types of image displays to differentiate image 50 from image 60, such as, for example, using different colors for images 50 and 60.

With reference again to Figure 6A, if image 60 represents an ideal golf stance, golfer 20 of Figure 2 would immediately be able to realize that his right shoulder is dipped too low, and that his legs are spread too far apart. Golfer 20 would then alter his stance and body position until image 50 matches image 60 as shown in Figure 6B.

With reference again to Figure 6A, in the present embodiment, the hands of image 50 are used as a common reference point with image 60. For example, if golfer 20 is in the act of a back swing and has raised his hands to his waist such that the hands of image 50 are at waist level, the hands of image 60 will also be at waist level. The rest of image 60 will then be located at the ideal position for a golfer whose hands are at waist level during a back swing. By sharing a common reference point, golfer 20 is always able to observe the position in which his body should be arranged at every point along his golf swing. That is, when the hands of golfer 20 are at shoulder level during a follow through, the hands of image 60 will also be at shoulder level, and golfer 20 is able to immediately determine how the rest of his body should be positioned when his hands are at shoulder level during a follow through. Although the hands are used as a common reference point in the present embodiment, the present invention is also well suited to using other portions of the golfer's body as a common reference point with image 60.

With reference still to Figure 6A, as an additional benefit of the present invention, golfer 20 of Figure 2 can also select to have image 60 perform the ideal golf swing at several different speeds. Specifically, image 60 can perform the golf swing at a much slower rate than normal in order to allow golfer 20 time to adjust his body position and movements accordingly. However, the present invention is also well suited to having image 60 perform the golf swing at the same speed as which the sample golfer would perform the golf swing. In so doing, the present invention makes it possible for golfer 20 to observe in real time the proper tempo of an ideal golf swing. For example, if image 50 of golfer 20 has finished his swing before image 60 has completed his swing,

golfer 20 knows that he must slow his swing in order to achieve an ideal tempo. Thus, the present invention not only provides for real time observation of body position and body movements during a golf swing, but also provides for real time observation of the tempo
5 of a golf swing.

Referring next to Figure 6C, another embodiment of the present invention is shown in which "fan" type displays of the position 51 of the golf club of golfer 20 of Figure 2 and the position 61 of the golf club of a sample golfer at different times during a
10 golf swing is shown. By displaying the position of the golf club at different times, golfer 20 is able to observe how the position 51 of his golf club differs from that of the ideal sample golfer. Thus, golfer 20 can observe in real time the difference in speed and tempo between his golf swing and an ideal golf swing. Although
15 only the position of the golf club is shown in Figure 6C, the present claimed invention is also well suited to displaying a fan type image showing the entire body or any portion thereof of golfer 20.

With reference next to Figure 7, another embodiment of the present invention is shown in which two images 50 and 60 are
20 displayed concurrently and overly each other on display unit 32. As in Figures 6A and 6B, image 50 represents the body position and body movements of golfer 20 of Figure 2. Image 60 again represents, for example, a stored record of the best previous golf swing of golfer 20, a golf swing of the instructor of golfer 20, or a
25 golf swing of a professional golfer whose body position and movements are stored in the memory of processor 30. By overlying the images as set forth in the present embodiment, golfer 20 can easily determine differences between his body position as represented by image 50 and the ideal body position as represented
30 by image 60.

With reference again to Figure 7, in the present embodiment, in order to further highlight the differences between image 50 and image 60, visual cues are indicated on display unit 32. These visual cues include, for example, "flashing" the
35 portions of image 50 which are positioned differently than ideal image 60. That is, the shoulders and legs of image 50 would flash

to indicate to golfer 20 of Figure 2 that his right shoulder is dipped too low and that his legs are spread too far apart. The flashing in the present embodiment may also be controlled such that the flashing would, for example, be more rapid the farther the improperly positioned portions of image 50 were from the desired position. By displaying these visual cues, the present claimed invention assists golfer 20 in realizing errors in his body position and his body movements during the performance of a golf swing. Although flashing is used as the visual cue in the present embodiment, the present invention is also well suited to various other types of visual cues such, for example color changes, or changes in the intensity of portions of image 50. When color changes are used as the visual cue, the color of image 50 would be, for example, green when image 50 matches ideal image 60, yellow when image 50 differs slightly from the positioning of image 60, and red when image 50 greatly differs from image 60.

With reference still to Figure 7, the present invention also allows golfer 20 of Figure 2 to adjust the sensitivity of the visual cues. That is, golfer 20 is able to program processor 30 of Figure 2 to only generate a visual cue such as, for example, flashing when the positioning of any portion of image 50 varies greatly from the positioning of image 60. In so doing, if golfer 20 is a beginner, he can decrease the sensitivity of the visual cues so that he is not alerted to minute differences between image 50 and image 60. However, as the skill of golfer 20 improves, he can heighten the sensitivity of the visual cues so that he is alerted to even minor differences between the positioning of image 50 and image 60. Thus, as golfer 20 improves he can "fine tune" his golf swing to almost completely match the ideal golf swing represented by image 60.

With reference again to Figure 7, although visual cues are used in the present embodiment, the present invention is well suited to the use of other cues such as for example audible cues. Such audible cues may include, for example, beeps or other sounds which are emitted from display unit 32 of Figure 2 when image 50 differs from image 60. Additionally, the present

invention changes the intensity or pitch of the beeps to indicate large or small variations in the position of image 50 from the position of image 60.

With reference next to Figures 8A and 8B, another
5 embodiment is shown in which the motion measurement apparatus of the present invention is used by golfer 20 as a "keyboard" or "mouse" in conjunction with display unit 32. Although used by a golfer in the present embodiment, the present invention is also well suited for use in other areas such as, for
10 example, as a head tracking apparatus in virtual reality application. Additionally, by attaching motion sensors to the head of a user using, for example, a headband, the present invention could also be employed as a "head mouse" for use by, for example, computer user. In such instances, calibration means and rate
15 control means are used to refine and translate motions of the head of a computer user to movement of, for example, a cursor or pointer on a computer screen.

With reference now to Figure 8A in the present embodiment, when golfer 20 raises only his left arm above his
20 head, a predetermined function is invoked and the present invention places a specific message on display 32. In the present embodiment, the "Club Select" function is displayed on display unit 32 when golfer 20 raises only his left arm above his head. As shown on display unit 32 of Figure 8A, the Club Select function
25 allows golfer 20 to indicate which club golfer 20 will be swinging by moving the position of window 68 over the desired club. In the present embodiment, golfer 20 may select from clubs ranging from the 1 wood (1W) to the putter (P). Although such a selection of clubs is available to golfer 20 in the present embodiment, the
30 present invention is also well suited to numerous variations on the number or types of clubs which may be selected.

With reference still to Figures 8A and 8B, in the present embodiment, golfer 20 moves the position of window 68 by moving his extended left arm nearer to or farther from his head. As
35 shown in Figure 8A, as golfer 20 moves his extended left arm away from his head, window 68 moves to the right or towards the

putter (P) on display unit 32. As shown in Figure 8B, when golfer 20 moves his extended left arm nearer his head, window 68 moves to the left or towards the one wood (1W) on display unit 32.

Although such movements and a Club Select function are set forth in the present embodiment, the present invention is also well suited to the use of numerous other types of functions which are selected and controlled using various other body positions and body movements.

With reference next to Figure 9, another embodiment of the present invention is shown in which a small vibrating mechanism 70 is attached to sensor 22 located on the knee joint 24 of golfer 20 of Figure 2. Vibrator 70 is electrically coupled to processor 30 of Figure 2. If images 50 of Figures 6A, 6B, and 7, differs from image 60, vibrators 70 on sensors 22 will vibrate those joints of golfer 20 which are improperly positioned. In so doing, golfer 20 is directly alerted as to which joints must be adjusted in order for image 50 to match image 60. Thus, golfer 20 is able to receive direct stimulation of his body only at those locations which are improperly positioned. In addition the present invention is also well suited to the attachment of a plurality of vibrating mechanisms to the body of golfer 20. For example, one vibrating mechanism may be placed at the front of knee joint 24, and a second vibrating mechanism may be located at the back of knee joint 24. If the knee of golfer 24 is bent too far, the vibrating mechanism on the front of the knee joint will be activated thereby instructing golfer 20 to straighten his knee. Likewise, if the knee of golfer 20 is too straight, the vibrating mechanism on the back of knee joint 24 will be activated thereby instructing golfer 20 to bend his knee. Although the use of multiple vibrating mechanisms is described in the present embodiment in conjunction with knee joint 24, multiple vibrating mechanisms may be employed in various combinations at numerous joints of golfer 20.

Furthermore, although a vibrating mechanism is set forth in the present embodiment, the present invention is also well suited to the use of other tactile stimuli such as, for example, a mild electric shocking mechanism.

With reference next to Figures 10A-10H, another embodiment of the present invention is set forth in which the structure of a motion measurement apparatus of the present invention is set forth in detail. Figure 10A is a rear view of a right handed golfer 20, having the present invention attached to his body. As shown in Figure 10A, a harness fits over the shoulders of golfer 20. Adjustable right and left shoulder brackets 101, 102 are attached to harness 100 using, for example, wing nuts, not shown, such that the position of right and left shoulder brackets 101, 102 may be adjusted to accommodate various shoulder widths. An upper back bracket 104 is also attached to harness 100 using, for example, wing nuts, not shown, such that the position of upper back bracket 104 may be adjusted to accommodate back sizes. A hip harness 106 is attached around the waist area of golfer. A lower back bracket 108 is attached to hip harness 106 using, for example, wing nuts, not shown, such that the position of lower back bracket 108 may be adjusted to accommodate various lower back sizes. Various potentiometers 110, 112 are coupled to upper back bracket 104. Likewise, various potentiometers 114, 116, and 118 are disposed on lower back bracket 108. A telescopic sliding torque transmitting lever connector 120 couples upper back bracket 104 and lower back bracket 108.

With reference next to Figure 10B a detailed perspective view of potentiometers 110, 112, potentiometers 114, 116, and 118, and telescopic sliding torque transmitting lever connector 120 are shown in detail. As shown in Figure 10B, potentiometers 110, 112, are coupled to upper back bracket 104 using, for example, clamps 122 and 124. All of the potentiometers of the present embodiment function in a similar manner. That is, as the potentiometer is rotated about its axis, the resistance within the potentiometer is altered. As a result, the outgoing voltage varies according to the amount of rotation to which the potentiometer is subjected. Thus, a precise measurement of the amount of rotation occurring at each potentiometer, and a corresponding portion of the body of golfer 20 of Figure 10A can be obtained. Wires, not shown,

electrically connect each of the potentiometers to a processor such as, for example, processor 30 of Figure 2.

With reference still to Figure 10B, potentiometer 110 measures the horizontal movement of the shoulders of golfer 20 of Figure 10A with respect to the spine of golfer 20. Potentiometer 112 is attached to clamp 122 such that potentiometer 112 measures the front-to-back movement of the shoulders of golfer 20 with respect to the spine of golfer 20. Telescopic sliding torque transmitting lever connector 120 delivers torque to potentiometer 114 such that the rotation of the spine of golfer 20 is quantitatively measured. Potentiometer 116 is attached to clamp 126 such that potentiometer 116 measures the front-to-back tilt of the spine of golfer 20 with respect to the hips of golfer 20. Finally, potentiometer 118 is attached to clamp 128 in order to measure changes in the position of the hips of golfer 20 with respect to the spine of golfer 20. Specifically, potentiometer 118 measures variations from the substantially perpendicular alignment of the spine of golfer 20 to the hips of golfer 20.

With reference again to Figure 10A, the left arm of golfer 20 also has a plurality of potentiometers 130, 131, 134, 140, 142, 148, 150, 152, clamp 132, bracket 102, harnesses 138, 146, and telescopic sliding torque transmitting lever connectors 136, 144, attached thereto.

With reference next to Figure 10C, a detailed description of the arrangement of potentiometers 130, 131, 134, 140, 142, 148, 150, 152, clamp 132, bracket 102, harnesses 138, 146, and telescopic sliding torque transmitting lever connectors 136, 144, attached to the left arm of golfer 20 of Figure 10A thereto is set forth. A potentiometer 130 is attached to clamp 132 connected to left shoulder bracket 102. Potentiometer 130 measures movement of the upper portion of the left arm of golfer 20 away from or towards the body of golfer 20. Also attached to potentiometer 130 is a potentiometer 134 for measuring the front-to-back motion of the left arm of golfer 20. Potentiometer 131 measures rotational movement of the upper left arm of golfer 20. A telescopic sliding

torque transmitting lever connector 136, is attached to potentiometer 134.

With reference still to Figure 10C, an elbow harness 138 has a potentiometer 140 attached thereto and coupled to telescopic
5 sliding torque transmitting lever connector 136 via a universal type joint configuration 137 in order to measure the rotation of the left upper arm of golfer 20. Additionally, elbow harness 138 has a potentiometer 142 attached thereto in order to measure the extension or bending occurring at the left elbow of golfer 20.
10 Furthermore, one end of a telescopic sliding torque transmitting lever connector 144 is coupled to potentiometer 142 using joint 147. A wrist harness 146 is attached to the left wrist of golfer 20 and has the second end of telescopic sliding torque transmitting lever connector 144 connected to a potentiometer 148 attached thereto.
15 Potentiometer 148 measures the rotation of the left wrist of golfer 20 with respect to the left elbow of golfer 20, and is coupled to potentiometer 150 which measures whether the wrist of the left hand of golfer 20 is held straight out from the lower arm or is bent up or down with respect to the lower arm of golfer 20. Finally,
20 potentiometer, 152 coupled to potentiometer 150 and wrist harness 146 measures whether the wrist of golfer 20 is held straight out, is bent inward such that the thumb on the left hand approaches the inside of the lower left arm, or whether the wrist is bent outward such that the small finger of the hand is bent towards the outside
25 of the lower left arm of golfer 20.

With reference next to Figure 10D, a view of the present invention taken along line D of Figure 10C is shown.

With reference next to Figure 10E a partial view of the present invention attached to the left leg of golfer 20 of Figure 10A
30 is shown. A left thigh clamp 154 is attached to lower back bracket 108. A potentiometer 156 measures the front-to-back motion of the left leg of golfer 20. Another potentiometer 158 measures the extent to which the left leg of golfer 20 is extended to the side away from the left side of golfer 20.

35 With reference again to Figure 10E, a strap 160 is placed around the left knee of golfer 20. An elastic connector 162 extends

from strap 160 to a lever arm 164. Lever arm 164 is coupled to a potentiometer 168 which measures the motion of the left knee of golfer 20. As shown in Figure 10E, a telescopic sliding torque transmitting lever connector 170 extends downwardly from the
5 outside of the left hip of golfer 20 towards the outside of the left ankle of golfer 20.

With reference next to Figure 10F, a bracket 172 is attached to a left foot harness 174 worn on the left foot of golfer 20. Attached to bracket 172 is a potentiometer 176 for measuring whether the
10 heel or toes of golfer 20 are pulled upward. Another potentiometer 178 measures the side to side motion of the foot of golfer 20. The motion of the right leg of golfer 20 is measured using a similar structure. Additionally, although not shown in the present embodiment, the present invention is well suited to having bracket
15 172 coupled directly to the ground, such that the ground can be used as a reference point for the positioning of golfer 20. Furthermore, although not shown, the present invention is also well suited to using means such as, for example, a gyroscope, a radio receiver, an optical system, or a magnetic link to provide a
20 quantitative measurement of the position of golfer 20 with respect to the ground and even with respect to a golf ball or golf club.

With reference next to Figure 10G, the attachment of the present invention to the right shoulder of golfer 20 is shown in detail. A potentiometer 180 is coupled to right shoulder bracket
25 101. Potentiometer 180 measures movement of the upper portion of the right arm of golfer 20 away from or towards the body of golfer 20. A second potentiometer 134 measures the front-to-back motion of the right arm of golfer 20 using a lever arm 184 having an elastic band 186 attached to elbow strap 188.

With reference next to Figure 10H, the positioning and movement of the right hand of golfer 20 on a golf club 189 is measured using a right wrist strap 190, and elastic band 192, a lever arm 194, and a potentiometer 196. Wrist strap 190 is connected using elastic band 192 to lever arm 194. Lever arm 194
35 is coupled to potentiometer 196 attached to golf club 189. In so

doing, the movement of the right hand of golfer 20 with respect to golf club 189 is quantitatively measured.

With reference next to Figure 11A, an alternate embodiment of the present invention is shown in which an alternate arrangement of potentiometers and lever arms is used to measure the movement of a joint of golfer 20. As shown in Figure 11, sensors such as, for example, potentiometers 202 and 204 are attached to lever arms 206 and 208 respectively. Lever arms 206 and 208 are then respectively connected to elastic bands 210 and 212 which in turn are connected to brackets 214 and 216 respectively. Potentiometer 200 is also coupled to potentiometer 218 via bracket 220. Assuming that the alternate arrangement of Figure 11 is attached to the back of golfer 20, then potentiometer 218 measures side to side motion of golfer 20, while potentiometers 202 and 204 measure front to back motion of golfer 20. Rotation of the back of golfer 20 is determined by the difference between the amount of rotation recorded at potentiometers 202 and 204. For example, if potentiometer 202 measures rotation, θ_{202} , and potentiometer 204 measures rotation, θ_{204} , then the rotation of the back of golfer 20, θ_{back} , is given by $\theta_{202} - \theta_{204}$.

With reference next to Figure 11B, an application of the alternate embodiment of Figure 11A is shown. Specifically, as described above in the discussion of Figures 8A and 8B, a head mouse 250 is shown attached to the head of a computer user 252. As shown in Figure 11B, motion sensors 254, 256, and 258 are coupled to a headband 260 worn by the computer user. Motion sensors 254, 256, and 258 are coupled using lever arms 262 and 264, and elastic bands 266 and 268 to for example a strap 270 worn on the back of computer user 252. Head mouse 250 is electrically coupled to a computer 272, such that motion of the head of computer user 252 translates into motion of a cursor or pointer 274 on a computer screen 276. A "mouse button", not shown, is mounted for example on a computer keyboard also not shown, for performing task associated with conventional mouses such as highlighting, dragging, and selecting, for example. In addition, head mouse 250 includes calibration means for initially placing

cursor 274 in a desired position on computer screen 276. Rate control means, not shown, are also provided to appropriately relate head movement of user 252 to movement of cursor 274.

Although sensors 254, 256, and 258 are coupled to headband 260 in the present embodiment, the present invention is also well suited to alternate configurations including having sensors coupled, for example to the back of the chair in which the user is sitting.

Additionally, the present invention is well suited to having at least one sensor positioned to measure "nodding" motions by the user.

Furthermore, the present invention is also well suited to head motion measurement configurations including but not limited to using two sensors and two levers, using two sensors and one lever.

With reference next to Figure 12, an alternate embodiment of the present invention is shown. Specifically, as described above in the discussion of Figure 10F, a motion measurement apparatus employing gyroscopic magnetometer or other self-referencing means 300 is shown. Self-referencing means 300 are placed for example in the upper back region of golfer 20. In so doing, self-referencing means 300 is able to provide output to processor means, not shown, in order to provide a quantitative measurement of the position of golfer 20 with respect to the ground and even with respect to a golf ball or golf club.

Thus, the present invention provides a compact, inexpensive system to monitor the movement of a human body while performing a motion such as, for example, a golf swing, which does not require the complex detection systems found in the prior art, and which provides for approximate real time observation of the body movement of a golfer while performing the golf swing. Additionally, the compact size of the present invention provides for portability which was not found in the prior art, thereby allowing the golfer to use the present invention wherever he desires.

The foregoing descriptions of specific embodiments of the present invention have been presented for purposes of illustration and description. They are not intended to be exhaustive or to limit

the invention to the precise forms disclosed, and obviously many modifications and variations are possible in light of the above teaching. The embodiments were chosen and described in order to best explain the principles of the invention and its practical application, to thereby enable others skilled in the art to best utilize the invention and various embodiments with various modifications as are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the Claims appended hereto and their equivalents.

IN THE CLAIMS:

1. An apparatus for measuring and visually displaying a user's body movement while performing a motion comprising:
 - 5 sensing means coupled to a user for quantitatively detecting movement of said user's body while performing a motion, and for generating signals indicative of said movement of said user's body while performing said motion,
 - processing means for receiving and processing said signals
10 generated by said sensing means, and
 - display means coupled to said processing means for receiving said processed signals from said processing means and graphically displaying at least one image representing said movement of said user's body which occurred while said user
15 performed said motion.
2. The motion measurement apparatus of Claim 1 wherein said sensing means further comprises:
 - 20 sensors coupled to said user's body at joints of said user's body which are moved while said user performs said motion, said sensors coupled to said joints of said user's body such that said sensors quantitatively measure the movement of said joints while said user performs said motion, said sensors coupled to said user's joints such that said sensors do not interfere with said
25 movement of said user's joints while said user performs said motion.
3. The motion measurement apparatus of Claim 2 wherein said sensing means further includes:
 - 30 flexible interconnection means for coupling adjacent said sensors such that said sensors are interconnected to form a single unit which is coupled to said user's body.
4. The motion measurement apparatus of Claim 2 wherein
35 said sensors are comprised of potentiometers.

5. The motion measurement apparatus of Claim 2 wherein said sensors are comprised of magnetic motion sensors.

6. The motion measurement apparatus of Claim 2 wherein
5 said sensors are comprised of optical motion sensors.

7. The motion measurement apparatus of Claim 2 wherein said sensors are comprised of stepper motors.

10 8. The motion measurement apparatus of Claim 1 wherein said processing means is disposed in a compact structure coupled to said body of said user.

9. The motion measurement apparatus of Claim 1 wherein
15 said processing means further includes:

memory means for receiving and storing sample signals corresponding to sample movement of a sample body when performing said motion.

20 10. The motion measurement apparatus of Claim 9 wherein said sample movement of said sample body and sample signals correspond to a prior performance of said motion by said user.

25 11. The motion measurement apparatus of Claim 9 wherein said sample movement of said sample body and said sample signals correspond to a performance of said motion by a second user.

30 12. The motion measurement apparatus of Claim 9 wherein said sample movement of said sample body and said sample signals correspond to an ideal performance of said motion.

35 13. The motion measurement apparatus of Claim 1 wherein display means graphically displays said at least one

image representing said movement of said user's body at approximately the same time said user performs said motion.

14. The motion measurement apparatus of Claim 1
5 wherein said display means graphically displays said at least one image representing said movement of said user's body after said user performs said motion.

15. The motion measurement apparatus of Claim 9
10 wherein said display means graphically displays concurrently said at least one image representing said movement of said user's body and a second at least one image representing said sample movement of said sample body's performance of said motion, such that said movement of said user's body can be compared with said
15 sample movement of said sample body's performance of said motion.

16. The motion measurement apparatus of Claim 15
wherein said first at least one image and said second at least one
20 image overlap each other.

17. The motion measurement apparatus of Claim 15
wherein said second at least one image corresponds to a prior performance of said motion by said user.
25

18. The motion measurement apparatus of Claim 15
wherein said second at least one image corresponds to a performance of said motion by a second user.

30 19. The motion measurement apparatus of Claim 15
wherein said second at least one image corresponds to an ideal performance of said motion.

20. The motion measurement apparatus of Claim 15
35 wherein said display means further includes:

means for visually indicating the difference between said at least one image representing said movement of said user's body and said second at least one image representing said sample movement of said sample body's performance of said motion.

5

21. The motion measurement apparatus of Claim 15 wherein said display means further includes:

means for audibly indicating when differences occur between said at least one image representing said movement of said user's body and said second at least one image representing said sample movement of said sample body's performance of said motion.

10

22. The motion measurement apparatus of Claim 15 wherein said sensing means further includes:

15

vibrational means for physically indicating when said movement of said user's body while performing said motion differs from said second at least one image representing said sample movement of said sample body's performance of said motion.

20

23. The motion measurement apparatus of Claim 15 wherein said sensing means further includes:

electric shock means for physically indicating when said movement of said user's body while performing said motion differs from said second at least one image representing said sample movement of said sample body's performance of said motion.

25

24. An apparatus for measuring and visually displaying a golfer's body movement while performing a golf swing comprising:

30

sensing means coupled to a golfer for quantitatively detecting movement of said golfer's body and a golf club while performing a golf swing, and for generating signals indicative of said movement of said golfer's body and said golf club while

35

performing said golf swing, said sensing means further comprising;

5 sensors coupled to said golfer's body at joints of said golfer's body which are moved while said golfer performs said golf swing, said sensors coupled to said joints of said golfer's body such that said sensors quantitatively measure the movement of said joints while said golfer performs said golf swing, said sensors coupled to said golfer's joints such that said sensors do not interfere with said movement of
10 said golfer's joints while said golfer performs said golf swing,
processing means for receiving and processing said signals generated by said sensing means, said processing means further including;
15 memory means for receiving and storing sample signals corresponding to sample movement of a sample golfer's body when said sample golfer performs said golf swing, and
display means coupled to said processing means for
20 receiving said processed signals and said sample signals from said processing means and graphically displaying at least one image representing said movement of said golfer's body and said golf club which occurred while said golfer performed said golf swing.

25

25. The golf swing measurement apparatus of Claim 24 wherein said sensing means further includes:

flexible interconnection means for coupling adjacent said sensors such that said sensors are interconnected to form a single
30 unit which is coupled to said golfer's body.

26. The golf swing measurement apparatus of Claim 24 wherein said sensors are comprised of potentiometers.

35 27. The golf swing measurement apparatus of Claim 24 wherein said sensors are comprised of magnetic sensors.

28. The golf swing measurement apparatus of Claim 24 wherein said sensors are comprised of optical sensors.

29. The golf swing measurement apparatus of Claim 24
5 wherein said sensors are comprised of stepper motors.

30. The golf swing measurement apparatus of Claim 24 wherein said sample movement of said sample golfer's body and sample signals correspond to a prior performance of said golf
10 swing by said golfer.

31. The golf swing measurement apparatus of Claim 24 wherein said sample movement of said sample golfer's body and said sample signals correspond to a performance of said golf
15 swing by a second golfer.

32. The golf swing measurement apparatus of Claim 24 wherein said sample movement of said sample golfer's body and said sample signals correspond to an ideal performance of said
20 golf swing.

33. The golf swing measurement apparatus of Claim 24 wherein display means graphically displays said at least one image representing said movement of said golfer's body at
25 approximately the same time said golfer performs said golf swing.

34. The golf swing measurement apparatus of Claim 24 wherein said display means graphically displays said at least one image representing said movement of said golfer's body after said
30 golfer performs said golf swing.

35. The golf swing measurement apparatus of Claim 24 wherein said display means graphically displays concurrently said at least one image representing said movement of said
35 golfer's body and a second at least one image representing said sample movement of said sample golfer's performance of said golf

swing, such that said movement of said golfer's body can be compared with said sample movement of said sample golfer's performance of said golf swing.

5 36. The golf swing measurement apparatus of Claim 35 wherein said first at least one image and second at least one image overlap each other.

10 37. The golf swing measurement apparatus of Claim 35 wherein said second at least one image corresponds to a prior performance of said golf swing by said golfer.

15 38. The golf swing measurement apparatus of Claim 35 wherein said second at least one image corresponds to a performance of said golf swing by a second golfer.

20 39. The golf swing measurement apparatus of Claim 35 wherein said second at least one image corresponds to an ideal performance of said golf swing.

 40. The golf swing measurement apparatus of Claim 35 wherein said display means further includes:

25 means for visually indicating the difference between said at least one image representing said movement of said golfer's body and said second at least one image representing said sample movement of said sample golfer's performance of said golf swing.

 41. The golf swing measurement apparatus of Claim 35 wherein said display means further includes:

30 means for audibly indicating when differences occur between said at least one image representing said movement of said golfer's body and said second at least one image representing said sample movement of said sample golfer's performance of said golf swing.

35

42. The golf swing measurement apparatus of Claim 35 wherein said sensing means further includes:

5 vibrational means for physically indicating when said movement of said golfer's body while performing said golf swing differs from said second at least one image representing said sample movement of said sample golfer's performance of said golf swing.

10 43. The golf swing measurement apparatus of Claim 35 wherein said sensing means further includes:

15 electric shock means for physically indicating when said movement of said golfer's body while performing said golf swing differs from said second at least one image representing said sample movement of said sample golfer's performance of said golf swing.

44. A method for measuring and visually displaying a user's body movement while performing a motion comprising the steps of:

20 coupling sensing means to a user for quantitatively detecting movement of said user's body while performing a motion, and for generating signals indicative of said movement of said user's body while performing said motion,

25 processing said signals generated by said sensing means, and

30 displaying on display means said processed signals wherein said display means graphically displays at least one image representing said movement of said user's body which occurred while said user performed said motion.

45. The motion measurement method as recited in Claim 44 wherein said step of coupling sensing means to a user further comprises the step of:

35 coupling sensors to said user's body at joints of said user's body which are moved while said user performs said motion, said sensors coupled to said joints of said user's body such that said

sensors quantitatively measure the movement of said joints while said user performs said motion, said sensors coupled to said user's joints such that said sensors do not interfere with said movement of said user's joints while said user performs said
5 motion.

46. The motion measurement method as recited in Claim 44 wherein said step of processing said signals generated by said sensing means further includes the step of:
10 receiving and storing sample signals in memory means, wherein said sample signals correspond to a sample movement of a sample body when performing said motion.

47. The motion measurement method as recited in Claim 15 44 wherein said step of displaying on display means said processed signals further includes the step of:
graphically displaying said at least one image representing said movement of said user's body at approximately the same time said user performs said motion.

20 48. The motion measurement method as recited in Claim 44 wherein said step of displaying on display means said processed signals further includes the step of:
graphically displaying concurrently on said display means
25 said at least one image representing said movement of said user's body and a second at least one image representing said sample movement of said sample body's performance of said motion, such that said movement of said user's body can be compared with said sample movement of said sample body's performance of said
30 motion.

49. The motion measurement method as recited in Claim 48 wherein said step of graphically displaying concurrently on said display means said at least one image representing said
35 movement of said user's body and said second at least one image further includes the step of:

visually indicating the difference between said at least one image representing said movement of said user's body and said second at least one image representing said sample movement of said sample body's performance of said motion.

5

50. The motion measurement method as recited in Claim 48 wherein said step of graphically displaying concurrently on said display means said at least one image representing said movement of said user's body and said second at least one image further includes the step of:

10

physically indicating at said joints of said user when said movement of said user's body while performing said motion differs from said second at least one image representing said sample movement of said sample body's performance of said motion.

15

51. An apparatus for measuring and visually displaying a golfer's body movement while performing a golf swing comprising:

20

sensing means coupled to a golfer for quantitatively detecting movement of said golfer's body and a golf club while performing a golf swing, and for generating signals indicative of said movement of said golfer's body and said golf club while performing said golf swing, said sensing means further

25

comprising;

30

sensors coupled to said golfer's body at joints of said golfer's body which are moved while said golfer performs said golf swing, said sensors coupled to said joints of said golfer's body such that said sensors quantitatively measure the movement of said joints while said golfer performs said golf swing, said sensors coupled to said golfer's joints such that said sensors do not interfere with said movement of said golfer's joints while said golfer performs said golf swing,

35

processing means for receiving and processing said signals generated by said sensing means, said processing means disposed in a compact structure coupled to said body of said golfer, said processing means further including;

5 memory means for receiving and storing sample signals corresponding to sample movement of a sample golfer's body when said sample golfer performs said golf swing, and

10 biofeedback means coupled to said processing means for receiving said processed signals and said sample signals from said processing means for indicating to said golfer differences between said signals generated by said movement of said golfer's body and said sample signals corresponding to said sample movement of said sample golfer's body.

15

52. An apparatus for measuring and visually displaying a user's body movement while performing a motion comprising:

20 sensing means coupled to a user for quantitatively detecting movement of said user's body while performing a motion, and for generating signals indicative of said movement of said user's body while performing said motion, said sensing means including self-referencing sensing means coupled to said user's body,

25 processing means coupled to said sensing means for receiving and processing said signals generated by said sensing means, and

30 display means coupled to said processing means for receiving said processed signals from said processing means and graphically displaying at least one image representing said movement of said user's body which occurred while said user performed said motion.

53. A head tracking apparatus for translating motion of a user's head into corresponding motion of a cursor on display means:

sensing means coupled to a user for quantitatively detecting movement of said user's head, and for generating signals indicative of said movement of said user's head,

5 processing means coupled to said sensing means for receiving and processing said signals generated by said sensing means, and

display means coupled to said processing means for displaying a cursor thereon, said display means able to vary the position of said cursor thereon in accordance with signals
10 received processing means.

54. The head tracking apparatus of Claim 53 wherein said processing means further comprises:

15 calibration means for initially positioning said cursor in a desired location on said display means, and

rate control means for selectively regulating motion of said user's head into corresponding movement of said cursor on said display means.

20 55. The head tracking apparatus of Claim 53 further comprising:

mouse button means coupled to said processing means for performing conventional mouse tasks on said display means.

25 56. An apparatus for measuring a user's body movement while performing a body motion comprising:

sensing means coupled to a user for quantitatively detecting movement of said user's body while performing a body motion, and for generating signals indicative of said movement of said
30 user's body while performing said body motion, said sensing means further comprising;

sensors coupled to said user's body at joints of said user's body which are moved while said user performs said body motion, said sensors coupled to said joints of said
35 user's body such that said sensors quantitatively measure the movement of said joints while said user

5 performs said body motion, said sensors coupled to said user's joints such that said sensors do not interfere with said movement of said user's joints while said user performs said body motion, and processing means for receiving and processing said signals generated by said sensing means.

57. An apparatus for measuring a user's body movement while performing a body motion comprising:

10 sensing means coupled to a user for quantitatively detecting movement of said user's body while performing a body motion, and for generating signals indicative of said movement of said user's body while performing said body motion, said sensing means further comprising;

15 at least two sensors coupled to said user's body, said at least two sensors having a first end of at least two respective lever arms coupled thereto,

20 at least two flexible connectors, each of said at least two flexible connectors having a first end thereof coupled to a second location of said user's body, said at least two flexible connectors having a second end thereof coupled to a second end of said respective at least two lever arms such that said sensors quantitatively measure the movement of said first and second locations of said user's body with

25 respect to each other while said user performs said body motion, said sensors coupled to said first and second locations of said user's body such that said sensors do not performs said body motion, and

30 processing means for receiving and processing said signals generated by said sensing means.




FIG. 1
(PRIOR ART)

2/20




FIG. 2

3/20




FIG. 3




FIG. 4

5/20




FIG. 5A

6/20




FIG. 5B

7/20




FIG. 6A

8/20




FIG. 6B

9/20




FIG. 6C

10/20




FIG. 7

11/20




FIG. 8A




FIG. 8B

12/20




FIG. 9

13/20




FIG. 10A

14/20






FIG. 10B

15/20






FIG. 10E




FIG. 10F

17/20




FIG. 10G




FIG. 10H




FIG. 11A




FIG. 11B

20/20




FIG. 12

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US95/06626

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :A61B 5/103

US CL :128/782

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 128/774, 779, 781, 782; 273/183.1,187.2

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
NONE

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
NONE

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US, A, 4,891,748 (MANN) 02 January 1990, see Fig. 1.	1-57
Y	US, A, 4,665,928 (LINIAL ET AL.) 19 May 1987, see Fig. 1.	1-7, 24-29, 44, 45, 51-53, 56, 57
Y	US, A, 4,912,638 (PRATT) 27 March 1990, see Fig. 1.	3, 25, 57
A	US, A, 5,249,967 (O'LEARY ET AL.) 05 October 1993.	1-57

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

<p>* Special categories of cited documents:</p>	
A document defining the general state of the art which is not considered to be part of particular relevance	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
E earlier document published on or after the international filing date	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
O document referring to an oral disclosure, use, exhibition or other means	*Z* document member of the same patent family
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search
07 AUGUST 1995

Date of mailing of the international search report
31 AUG 1995

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

MAX HINDENBURG

Telephone No. (703) 308-3130

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US96/19209

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : GO9G 5/00

US CL : 345/156,158; 414/2,5

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 345/156,158; 414/2,5

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,184,319 A (KRAMER) 02 February 1993, col. 3, line 25 to col. 10, line 35.	1-24
Y	US 4,731,603 A (MCRAE et al) 15 March 1988, col. 8, line 64 to col. 9, line 34 and Fig. 6.	1-24

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	* T	later documents published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
* A* document defining the general state of the art which is not considered to be part of particular relevance	* X*	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
* B* earlier documents published on or after the international filing date	* Y*	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
* L* document which may throw doubt on priority claim(s) or which is cited to establish the publication date of another citation or other special reasons (as specified)	* A*	document member of the same patent family
* O* document referring to an oral disclosure, use, exhibition or other means		
* P* document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

19 FEBRUARY 1997

Date of mailing of the international search report

19 MAR 1997

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
PCT
Washington, D.C. 20231

Tele No. (703) 305-3230

Authorized officer

REGINA LIANG

Telephone No. (703) 305-4719

ISA/210 (second sheet)(July 1992)

THIS PAGE BLANK (USPTO)